CPL Remote Security System

Owner's Manual

FCC COMPLIANCE

This device complies with Part 15 of the FCC rules and with RSS-210 of Industry Canada. Operation is subject to the following two conditions:

1. This device may not cause harmful interference, and

2. This device must accept any interference received, including any interference that may cause undesired operation.

Warning!

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

* Features & Specifications may change without notice

Table of Contents

Features and Benefits 3

Using Your Remote Transmitter 4-5
- Arming the Security System
- *Pre-arm Mode*
- Disarming the Security System
- *Attempted Intrusion Identification*
- Disabling the IT-s™ Interior Theft Sensor
- Activating the Trunk Release Feature
- Personal Protection Alarm
- Using Valet Mode

When Your Security System is Triggered 6

Automatic Convenience Options 6

The Interior Status Indicator 6

System Maintenance 7
- Changing the Remote Control Battery
- Adding Remote Controls to Your System
- Deleting Lost or Stolen Remote Controls from Your System

Basic Troubleshooting 8

Emergency Disarm Procedure 9

Code Alarm Warranty Plan 10

Two Easy-to-Use Weather-Resistant Remote Controls

The remote controls included with the CPL Security System utilize durable, moisture resistant cases and sealed rubber buttons for reliability and long life. Rolling code technology prevents the transmitter signals from being duplicated. The button functions are clearly labeled to make the system simple to operate.

All Entrances Protected

Opening any door or entrance protected by the security system triggers the vehicle horn and flashes the vehicle parking lights.

Starter Disable

The CPL Security System protects your vehicle from theft by disabling the starter when the system is armed.

IT-s™ Interior Theft Sensor

This patented sensor uses infra-red technology to reliably detect vehicle impact associated with attemted intrusion. The IT-s™ sensor guards against vehicle body damage, and theft of vehicle's equipment (such as airbags) and personal belongings.

Remote Keyless Entry

The CPL Security System conveniently locks and unlocks vehicle doors and opens the trunk or hatch by remote control.*

Personal Protection Features

Remote Panic Alarm is among an array of features that enhance personal safety.**

Interior Status Indicator

The bright-red warning light is an effective visual deterrent to a would-be thief.

Car Find

Use the Car Find feature to locate your vehicle in a crowded parking lot.The horn will emit 5 short honks when the find feature is activated

IMPORTANT NOTE: The operation of the CPL Security System as described in this manual is applicable to most vehicles. However, due to the engine type and configuration of some vehicles (i.e. diesel engines), some functions AND/OR SAFETY PRECAUTIONS may not apply. Please see your installing dealer for more information.

* If vehicle is equipped with power door locks and they are connected to the alarm system by your installer.

** May require additional connections, components, and/or charges. See your installer for details.



Arming the Security System

To arm the system, exit the vehicle, close all doors, then press* the ARM button. The horn** will "honk" twice† and the parking lights will flash twice, indicating the system is armed. The doors will also lock at this time (if equipped and connected). The status indicator (red warning light on the dash) will blink steadily, once per second.

Pre-arm Mode

If the horn "honks" and the parking lights flash only once, this indicates that the vehicle courtesy light is on, or that a protected entry point is not closed securely. Check to see that doors, hood, and trunk are properly closed. Once all entrances are secured (and the courtesy light is off), the system will "honk" / flash again. The system is now fully armed. (If the entrance is not secured within 4 minutes, the system will arm and ignore the unsecured entrance until it is closed.)

Disarming the Security System

To disarm the system, press the DISARM button. The horn will "honk" and the parking lights will flash once, and the doors will unlock. The courtesy light will turn on for 1 minute, or until the vehicle is started.

Attempted Intrusion Identification

If the horn "honks" four times when disarming, this indicates that the system was triggered in your absence. The status indicator will also flash rapidly. Perform the following operation to determine the protected zone that triggered the system:

After disarming, press the emergency override button. The horn will "honk" to indicate the cause of the alarm trigger:

1 honk	IT-s Interior Theft Sensor
2 honks	Door
3 honks	Hood
4 honks	Trunk/Optional Sensors
5 honks	Ignition was turned on

* Throughout this manual, 'press' refers to pressing for less than 1 second; 'press and hold' refers to pressing for more than 1 second.

** If you have chosen the Silent Arming Option, the horn will not sound when arming or disarming until the appropriate button is pressed a second time.

Disabling the IT-s™ Interior Theft Sensor

It may be necessary at times to disable the IT-s™ Interior Theft Sensor, especially when parking in areas (like parking garages) where extreme vibration may cause false alarms. Press the ARM button. Then press the both buttons within two seconds, to disable the interior theft sensor**.** The horn will chirp four times to indicate that the sensor is disabled. The sensor will become enabled again the next time the system is armed normally.

Activating the Trunk Release Feature

Press and hold the DISARM button to open the vehicle trunk or hatch (if equipped and connected). This button is sometimes used to operate another accessory, the accessory will stay active for as long as the button is held.

Personal Protection Alarm (Panic)

Press and hold both buttons to activate the vehicle horn and parking lights for 30 seconds. Press any remote control button to turn off the Panic alarm.

Using Valet Mode

If the Passive Arming feature is enabled on your system, Valet mode temporarily prevents the alarm system from arming automatically. This is useful when fueling or servicing your vehicle.

To enter Valet Mode:

With the vehicle ignition on, press the ARM & DISARM buttons simultaneously. The red dashboard warning light (status indicator) will turn on for one second, then turn off. This indicates that the system is in Valet mode.

Note: In Valet mode, all keyless entry and convenience features operate normally. (The LED will falsh a double pulse)

To exit Valet Mode:

With the vehicle ignition on, press the ARM & DISARM buttons simultaneously The red dashboard warning light (status indicator) will turn on for one second, then turn off. This indicates that the system has exited Valet mode.

Hint: To prevent your security system from automatically arming while unloading or refueling your vehicle, without placing the system in Valet mode, simply press the disarm button on your remote control transmitter after turning the ignition key off. Doing so places your system into a temporary or onetime Valet mode. Next time you exit your vehicle the system will arm in the normal manner.

Automatic Convenience Options

The CPL Security System performs a variety of automatic functions to enhance security and comfort. Some of these features are programmable at the time of installation. Please see your installer for further details.

Automatic Arming

The CPL Security System will arm automatically 1 minute after the ignition is turn off. This feature can be temporarily disabled by placing the system into Valet mode. (If option is selected)

Ignition Lock

If all doors are closed and the vehicle is started with the key, the doors will automatically lock.

Ignition Unlock

When the ignition is turned off, the doors will automatically unlock.

When Your Security System is Triggered

The CPL Security System will trigger if one of the following events occurs while the system is armed:

- Any protected entrance is opened
- The vehicle ignition is turned on
- The vehicle is jolted hard enough to signal the impact detector

Once the alarm is triggered, the horn will sound and the vehicle parking light will flash for 30 seconds. The system will then re-arm, awaiting the next intrusion attempt. To stop the horn from sounding while keeping the alarm armed and doors locked: press the ARM button while the system is triggered.

The Interior Status Indicator

The Status Indicator is a high-intensity red light mounted in a visible location on the vehicle dashboard. This red light gives a visual indication of the alarm system's state of operation. Note the chart below:

If the Status Indicator is...	....then the Security System
Off	is disarmed
Flashing Slowly	is armed
Flashing Very Quickly	was triggered in your absence (see Attempted Intrusion ID - page 4)
Flashing Intermittently (2 flashes, off, 2 flashes)	is in Valet mode
On (not flashing)	is in Pre-arm mode

Changing the Remote Control Battery

The 12-volt alkaline battery supplied in your remote transmitter should last approximately one year, depending on usage. When the battery begins to weaken, you will notice a decrease in range, or the distance from your vehicle that your remote transmitter will operate. Follow the instructions below to change the remote transmitter battery.

1. Using a coin pry off the back of the transmitter (the transmitter snaps together) and expose the battery.

2. Remove the old battery and replace with GP-23A or equivalent. Be sure to observe the (+) and (-) signs in the battery compartment.

3. Replace the case backing, then test the remote transmitter. **It is not necessary to re-program the remote transmitter after changing the battery.**

Adding Remote Controls to Your System

The CPL Security System has the ability to operate from up to four (4) remote controls. Follow these instructions to add a remote control to your system.

1. Make sure the system is disarmed and the ignition is off.
2. Open the driver's door.
3. Turn vehicle ignition on.
4. Press and hold emergency override button.
   After 15 seconds, the horn will sound three (3) times. This indicates that the unit has entered the remote control programming mode.
5. Release the button.
6. Press the ARM button (button 1) on the remote control to be programmed.
   The horn will sound once, indicating that the system has "learned" that remote control.
7. Repeat step 6 for any additional remote controls.
8. Turn the vehicle ignition off to exit the programming mode. Test all remote controls to ensure that they work properly.

Deleting Lost or Stolen Remote Controls from Your System

If one of your remote controls is lost or stolen, follow these instructions IMMEDIATELY to remove the control code from your system.

1. Have all remaining remote controls available.
2. Enter the control programming mode by following steps 1 - 5 of ***Adding Remote Controls to Your System***.

3a. **If you have only one remaining remote control,** press the ARM button on that remote control **four (4) times,** pausing at least 1 second in between each press. The horn must "honk" each time you press the ARM button.

3b. **If you have two remaining remote controls,** press the ARM button on each remote control **two (2) times,** pausing at least 1 second in between each press. The horn must "honk" each time you press the ARM button.

3c. **If you have three remaining remote controls,** press the ARM button on one remote control **twice,** then press the ARM button on the remaining remote control once**.** Pause at least 1 second in between each press. The horn must "honk" each time you press the ARM button.

4. Turn the vehicle ignition off to exit the programming mode. When you are finished, the lost or stolen remote control will no longer operate your system.

Basic Troubleshooting

This section outlines some of the basic issues you may experience

This section outlines some of the basic issues you may experience while becoming used to the CPL Security System. If you have a problem that is not covered by this section, please consult your installer.

Symptom	Problem	Solution
Remote control does not work	Weak or dead battery	Change battery
	Remote control not programmed	Program remote control (page 7)
System will not arm	Door or other entrance is open	Close entrance
	Courtesy light is on	Turn courtesy light off
	System is in Valet mode	Turn off Valet mode (page 5)

Emergency Disarm Procedure

If your remote control is lost or fails to function, use this procedure to disarm the CPL Security System and start your vehicle.

1. Use the keys to enter the vehicle.
   The alarm will sound once the door is opened.
2. Insert the key into the ignition and turn to the ON position.
3. Locate and press the emergency override button.
   The alarm will turn off and then you will be able to start your vehicle.

To enter in and out of VALET without a remote transmitter.Turn the ignition ON and OFF three (3) times.

Your Emergency Disarm Button is located:

Installer Programmed Options

Ignition On Door Lock	ON	OFF
Ignition Off Door Unlock	ON	OFF
Siren/Horn Chirps	ON	OFF
Passive Arming	ON	OFF

Code Systems, Inc. Limited Lifetime Warranty

A Code Systems Inc. (“CODE”) vehicle security system sold to a retail consumer purchaser by an authorized dealer of CODE and installed by an authorized dealer of CODE is warranted by CODE to the original retail consumer purchaser to be free from defects in workmanship and materials for the lifetime of the vehicle in which the security system was originally installed.

A CODE vehicle security system sold to a retail consumer purchaser by an authorized dealer of CODE and installed by a party other than an authorized dealer of CODE is warranted by CODE to the original retail consumer purchaser to be free from defects in workmanship and materials for the lifetime of the vehicle. Defects caused by or related to the improper installation of the security system are not covered by this or any other warranty.

The duration of this warranty described above applies to all components of the security system except for: switches, indicator lights, transmitter(s) and accessories purchased separately.

Transmitters, exclusive of the transmitter case, are warranted by CODE to the original retail consumer purchaser to be free from defects in workmanship and materials for the lifetime of the of the vehicle in which the security system was originally installed.

Switches, indicator lights, and transmitter cases are warranted to the original consumer purchaser for a period of one (1) year from the date of purchase when the system is installed by an authorized CODE dealer.

Security system accessories are covered by the warranty supplied with the accessory. Wiring harnesses altered by installation and transmitter batteries are not covered by this or any other warranty.

This warranty is non-transferable, non-assignable and is completely voided when the security system is removed from the car in which it was originally installed. If the vehicle in which the security system was originally installed in is transferred to another party, this warranty no longer applies.

This warranty does not apply to any product damaged by accident, physical or electrical abuse, improper installation, alteration, any use contrary to its intended function, unauthorized service (i.e. service by anyone other than CODE or its authorized service personnel), fire, flood, lightning or other acts of God.

Should a product be found to be defective during the warranty duration, CODE will repair or replace the product or any part of the product that CODE agrees is defective without charge to the retail consumer purchaser of the product during the first year of the warranty period. After the first year of the warranty period has expired CODE will repair or replace the product or any part of the product that CODE agrees is defective for a fee of $10.00 to cover shipping and handling charges.

In order for a product to be repaired or replaced under the terms of this warranty, the defective product must be returned to an authorized CODE dealer and accompanied by a copy of the original retail sales receipt. The date of purchase and year, make and model of the vehicle in which the security system was originally installed in must be clearly indicated on the sales receipt.

CODE shall not be held responsible for any removal and/or reinstallation charges of a defective product, damage to or theft of the vehicle or its contents, or any incidental or consequential damages caused by any failure of the product to function properly. Under no circumstances should this warranty, or product covered by it, be construed as an insurance policy against loss. CODE neither assumes nor authorizes any person or organization to make ANY WARRANTIES or assume any liability in connection with the sale, installation, or use of this product. This is the complete CODE warranty and no other warranty exists.

The warranty identified in this form is exclusive and CODE makes no other warranties expressed or implied for any goods or services provided by CODE. CODE specifically and expressly excludes any other warranties including the fitness for a particular purpose and all warranties of merchantability. The customers sole and exclusive remedy for any and all claims against CODE arising out to the customers use of any CODE vehicle security system or component shall be as delineated in the warranty set forth above. CODE shall not be liable to any customer or any other person or entity for any direct or indirect, consequential, special or exemplary damages arising out of or in connection with the customers use of, or inability to use, or misuse of any CODE provided product.

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.